

Printec® Premium Laminating Film

M LAM SUP MAT / M LAM SUP GL

Technical Information Sheet

PVC

Type	Calendared monomeric soft PVC film
Thickness	80µm ±10µm
Softness	28 PHR

Adhesive

Type	Clear solvent based permanent pressure sensitive
Thickness	20µm ±3µm
Adhesion Temperature	15°C~40°C
Peeling Force on SUS	≥1280/25mm 20min
Peeling Force on Glass	≥860/25mm 20min
Peeling Force on Lacquer	≥1080/25mm 20min

Liner

Type	One side PE treated premium paper
Color	White
Weight	100g±5 g/m ²
Release Force	15 g/inch

Storage Period:

2 Years under ordinary condition at temperature of 22°C and relative humidity of 50-55%

Shrinkage:

Shrinkage less than 2% without printed ink at outdoor use for one year.

Attention:

Data above are updated results and conclusions of test by Printec® and is subject to change without prior notice.

After printing the ink must be thoroughly dry in order to avoid any affect on the later combination with the laminate. Surface of the printed material on which the laminating film will be applied must be thoroughly cleaned from dust, Grease or any contamination which could affect the adhesion of the material. The compatibility of selected materials and inks should be tested by the user, prior to application of the material.

Printec® is not responsible for all the performance of this material for a given application, the users of materials should perform their own testing to determine the suitability of the material for the intended use.