

Printec® Self Adhesive Vinyl With Grey Back

MO FOLYO MT/GRİ - MO FOLYO M/G 100m - MO FOLYO GL/GRİ - MO FOLYO G/G 100m

Technical Information Sheet

PVC

Type	Calendared monomeric soft PVC film
Thickness	80mic ±10um
Color Code	Ceramic white
Shrinkage	≤0.8%
Surface Tension	≥30dn/cm
Opacity	>80%
Flow mark	without

Adhesive

Type	Grey solvent based permanent pressure sensitive
Weight (g/m ²)	22±2
Adhesion Temperature	15°C~40°C
180° Peeling Force	≥18N/25mm 20min (GB2792-81)
Initial Adhesion-Ball Tack	≥5 Steel Ball (GB4852-84)
Holding Power	≥800min (GB4854-84)

Liner

Type	Kraft Paper
Color	White
Weight	120g±5 g/m ²
Release Force	0,1~0,6 N/4cm

Storage Period:

2 Years under ordinary condition at temperature of 22°C and relative humidity of 50-55%

Attention:

Data above are updated results and conclusions of test by Printec® and is subject to change without prior notice.

After printing the ink must be thoroughly dry in order to avoid any affect on the later combination with the laminate. Surfaces to which the material will be applied must be thoroughly cleaned from dust, Grease or any contamination which could affect the adhesion of the material. Freshly lacquered or painted surfaces should be allowed to dry for at least three weeks and to completely cure respectively. The compatibility of selected lacquers and paints should be tested by the user, prior to application of the material.

Printec® is not responsible for all the performance of this material for a given application, the users of materials should perform their own testing to determine the suitability of the material for the intended use.