

## Technical Information Sheet

### PVC

Type	Calendared monomeric soft PVC film
Thickness	140µm ±10µm
Color Code	White
Shrinkage	≤0.6%
Opacity	>99%
Hole Count	Average 20 /cm <sup>2</sup>
Hole Diameter	1,6mm
Distance Between Holes	2,4mm
Hole Space	41%

### Adhesive

Type	Clear solvent based pressure sensitive
Weight (g/m <sup>2</sup> )	16±2
Adhesion Temperature	15°C~40°C
180° Peelilng Force	≥3N/25mm 20min (GB2792-81)
Initial Adhesion-Ball Tack	≥5 Steel Ball (GB4852-84)
Holding Power	≥800min (GB4854-84)

### Liner

Type	Kraft Paper
Color	White
Weight	140g±5 g/m <sup>2</sup>
Release Force	0,05±0,02 N/25mm

### Storage Period:

2 years under ordinary condition at temperature of 22 °C and relative humidity of 50-55%

### Guarantee:

2 years under ordinary circumstances (not after use of strong cleaning chemicals, etc.) Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination which could affect the adhesion of the material and it must be done in dry weather conditions. (Removability is not covered in the guarantee)

### Attention:

Data above are updated results and conclusions of test by Printec® and is subject to change without prior notice.

Printec® is not responsible for all the performance of this material for a given application, the users of materials should perform their own testing to determine the suitability of the material for the intended use.